



MATERIAL SAFETY DATA SHEET

Product name: Safety Boosters
Description: 22, 25, and 27 caliber blank cartridges for powder actuated fastening tools
Supplier: Hilti, Inc. P.O. Box 21148, Tulsa, OK 74121; phone 1800 879 8000
Emergency # (Chem-Trec.): 1 800 424 9300 (USA, PR, Virgin Islands, Canada); 001 703 527 3887 (other countries)

INGREDIENTS AND EXPOSURE LIMITS

Ingredients:	CAS Number:	TLV:	PEL:	STEL:
Nitroglycerin	00055-63-0	0.46 mg/m ³ (S)	NE	2 mg/m ³ (S)
Nitrocellulose	09004-70-0	NE	NE	NE
Lead styphnate	15245-44-0	0.05 mg/m ³ *	0.05 mg/m ³ *	NE
Barium nitrate	10022-31-8	0.5 mg/m ³	0.5 mg/m ³	NE
Tetracene	00109-27-3	NE	NE	NE

Abbreviations / Symbols: * exposure limit for metallic lead. **NE** = None Established. **NA** = Not Applicable. **(S)** indicates exposure should be controlled for the cutaneous routes including the mucous membranes, eyes, and skin. Airborne exposures as well as direct contact must be considered.

PHYSICAL DATA

Appearance:	Blank brass cartridges.	Odor:	None.
Vapor Density: (air = 1)	Not applicable.	Vapor Pressure:	Not applicable.
Boiling Point:	Not applicable.	VOC Content:	Not applicable.
Evaporation Rate:	Not applicable.	Solubility in Water:	Not applicable.
Specific Gravity:	Not applicable.	pH:	Not applicable.

FIRE AND EXPLOSION HAZARD DATA

Flash Point:	Not applicable.	Flammable Limits:	Not applicable.
Extinguishing Media:	Water.		
Special Fire Fighting Procedures:	Flood area with water or keep cartridges cool with water spray.		
Unusual Fire and Explosion Hazards:	Cartridges can blast if exposed to temperatures > 160°C. Mass detonation will not occur.		

REACTIVITY DATA

Hazardous Polymerization:	Will not occur.	Stability:	Stable.
Incompatibility:	Strong acids and oxidizing agents.		
Decomposition Products:	Oxides of nitrogen, oxides of carbon, acrid fumes and lead oxide.		
Conditions to Avoid:	Acids, excessive heat, crushing, and electrical currents.		

HEALTH HAZARD DATA

Known Hazards:	OSHA has established an action level of 0.03 mg/m ³ for lead. Exposures that exceed recommended limits for lead may be possible under certain conditions such as excessive firing with little air movement and/or firing in small enclosed work areas. Chronic (long-term) overexposure to lead can result in damage to blood-forming, nervous, urinary and reproductive systems.
Signs and Symptoms of Exposure:	Excessive exposure to gases might cause irritation to the eyes, skin, and respiratory system. Adverse health effects are not expected from acute exposure to fumes and gases; however, adequate ventilation, personal protective equipment, and/or good personal hygiene practices are essential to keep exposure to a minimum.
Routes of Exposure:	Dermal. Inhalation.
Carcinogenicity:	Organic lead compounds are not classified by IARC or NTP as carcinogens. Lead styphnate is converted to metallic lead and lead oxide during combustion. Metallic lead and lead oxide have not been tested adequately.
Medical Conditions Aggravated by Exposure:	None anticipated.

EMERGENCY AND FIRST AID PROCEDURES

Eyes:	If irritation occurs, flush with plenty of water. Consult a physician if symptoms persist.
Skin:	Practice good hygiene; i.e. wash with soap and water after using and before smoking/eating.
Inhalation:	Move victim to fresh air. Get medical attention if symptoms persist.
Ingestion:	Get immediate medical attention.
Other:	Referral to a physician is recommended if there is any question about the seriousness of the injury/exposure.

CONTROL MEASURES AND PERSONAL PROTECTIVE EQUIPMENT

Ventilation:	General (i.e., natural or mechanically induced fresh air movements that maintain vapor concentrations below recommended exposure limits).
Eye Protection:	Suitable safety glasses with side-shields, or safety goggles.
Skin Protection:	Cleaning powder actuated tools can result in some exposure to lead compounds. Impermeable gloves are recommended. Wash hands thoroughly when finished and before eating or smoking.
Respiratory Protection:	Not normally required. Where air movement is inadequate to maintain exposure below recommended levels, wear a high efficiency particulate respirator.
Other:	Hearing protection should be worn when firing powder actuated tools

PRECAUTIONS FOR SAFE HANDLING AND USE

Handling and Storing Precautions:	Store in a cool dry place. Do not crush or drop. Keep away from excessive heat, electrical current, strong acids and oxidizers. NFPA 495 requires 15 feet separation (or 1-hour firewall) from flammable liquids, flammable solids, and oxidizers. For industrial use only. Keep out of reach of children. Use with adequate ventilation. Practice good hygiene; i.e. wash after using and before eating or smoking.
Other Precautions::	Use only in powder actuated tools designed to handle these boosters. Construction industry employees must be properly trained as prescribed by OSHA regulations 29 CFR 1926.302 (e). All employees should be familiar with the safe operating procedures and requirements for powder operated tools as described in ANSI A10.3 and OSHA 29 CFR 1910.243 (d).

REGULATORY INFORMATION

Hazard Communication:	This MSDS has been prepared in accordance with the federal OSHA Hazard Communication Standard 29 CFR 1910.1200.
HMIS Codes:	Health 1, Flammability 1, Reactivity 3, PPE B (Glasses, Gloves)
DOT Shipping Name:	Limited Quantity - LQ
ICAO / IATA Shipping Name:	Cartridges. Power device, Class 1.4S, UN 0323
TSCA Inventory Status:	Chemical components listed on TSCA inventory.
SARA Title III, Section 313:	This product contains < 1% lead styphnate (CAS No. 15245-44-0), < 0.1% barium nitrate (CAS No. 10022-31-8), and 5 - 11% nitroglycerin (CAS No. 55-63-0) which are subject to the reporting according to Section 313 of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR part 372.
Waste Disposal Methods:	Misfires should be stored in a closed container until disposal or as otherwise required by local, state, and federal safety, health and environmental regulations. The recommended disposal method is an explosives incinerator.
EPA Waste Code(s):	D008

CONTACTS

Customer Service:	1 800 879 8000
Technical Service:	1 800 879 8000
Health / Safety:	1 800 879 6000 Jerry Metcalf (x1003704)
Emergency # (Chem-Trec):	1 800 424 9300 (USA, PR, Virgin Islands, Canada); 001 703 527 3887 (other countries)

The information and recommendations contained herein are based upon data believed to be correct; however, no guarantee or warranty of any kind expressed or implied is made with respect to the information provided.



SAFETY DATA SHEET

Prepared to U.S. OSHA, CMA, ANSI, Canadian WHMIS, Australian WorkSafe, Japanese Standard JIS Z 7250:2000, and EU REACH Regulations

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name: **CARTRIDGES - FOR TOOLS, BLANK or CARTRIDGES, POWER DEVICES**
CAS Number: Mixture – Metal Alloy
Synonyms: Centerfire Powertool Loaded Round, Rimfire Cartridge for Power Device, 22, 25, 27, 32, 38 Caliber Powertool Round, Power Load, Blank Power Load and/or Booster, Powder Load, Cartridges for Tools, Blank
Product Use: Centerfire Powertool Loaded Round
U.N. Number: UN 0014 or UN 0323
U.N. Dangerous Goods Class Explosive, 1.4S
Manufacturer/Responsible Party: Olin Winchester, LLC
Manufacturers' Address: 600 Powder Mill Road, East Alton, IL 62024 www.winchester.com
Emergency Telephone Number: US/Canada: 1-800-424-9300
Outside US/Canada: 703-527-3887
SDS Control Group: 618-258-3507 (Technical Information Only)

Olin SDS No.: 00102.0001

Issue Date: 6/1/15

Revision Date: 002/28/2019

Revision No.: 5

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW: EXPLOSIVE. KEEP AWAY FROM HEAT. DO NOT SUBJECT TO MECHANICAL SHOCK. PARTICLES FROM FIRING MAY BE HARMFUL IF INHALED. DO NOT TAKE INTERNALLY.

US DOT SYMBOLS



CANADA (WHMIS) SYMBOLS

This Product is not subject to WHMIS

Class 6 Explosive

GHS HAZARD SYMBOLS

**GHS Classifications:**

Carcinogenicity Category 1A
 Reproductive Toxicity Category 1A
 Explosive Division 1.4
 STOT RE Category 1
 Aquatic Environment, Chronic II

Signal Word:

Danger

Hazard Statements :

H204: Fire or projection hazard
 H350: May cause cancer
 H360: May damage fertility or the unborn child
 H362: May cause harm to breast-fed children
 H372: Causes damage to nervous system, kidney, and hematopoietic system through prolonged or repeated exposure
 H360: May damage fertility or the unborn child
 H411: Toxic to aquatic life with long lasting effects

Target organs:

Nervous, renal and hematopoietic systems

Precautionary Statements:

P102: Keep out of reach of children
 P210: Keep away from heat/sparks/open flame/hot surfaces
 P250: Do not subject to shock/friction
 P260: Do not breathe dust/fume/gas/mist/vapors/spray
 P264: Wash hands thoroughly after handling
 P270: Do not eat, drink or smoke when using this product
 P271: Use only outdoors or in a well-ventilated area
 P273: Avoid release to the environment
 P280: Wear protective gloves/protective clothing/eye protection/face protection

GHS Pictograms:

Explosive; Pictogram: exploding bomb
 Specific Target Organ Toxicity; Pictogram Code: GHS08
 Environment; Pictogram Code: GHS09

EU Classifications:

Hazard Symbols	E, T, N
Risk Phrases	R2: Risk of explosion by shock, friction, fire or other sources of ignition R45 (Category 1): May cause cancer R48: Danger of serious damage to health by prolonged exposure R60/61 (Category 1): May impair fertility or cause harm to the unborn child R63: Possible risk of harm to the unborn child R64: May cause harm to breast-fed children R51/53: Toxic to aquatic organisms and many cause long-term adverse effects in the aquatic environment
Safety Phrases	S2: Keep out of reach of children S15: Keep away from heat S20/21: When using do not eat, drink or smoke S22: Do not breathe dust S39: Wear eye/face protection S51: Use only in well-ventilated areas S61: Avoid release to the environment

Health Hazards or Risks From Exposure

This product is composed of a finished metal alloy cartridge which contains the various components completely sealed within. Therefore, under normal handling of this product, no exposure to any harmful materials will occur. When the product is fired, a small amount of particles may be generated which may be slightly irritating to the eyes and the respiratory tract. The particles may contain trace amounts of these harmful substances:

Lead: Ingestion of large amounts of lead can cause abdominal pain, constipation, cramps, nausea and/or vomiting. Chronic exposure to lead can cause kidney damage, anemia, reproductive effects, developmental effects and permanent nervous system damage in humans including changes in cognitive function. Occupational exposure to lead is associated with lung and stomach cancer. Lead is classified as a probable human carcinogen.

Nitroglycerin: Will produce dilation of blood vessels and drop in blood pressure which may affect the heart. It has also been shown to cause methemoglobinemia (cyanosis).

Copper: Inhalation of high concentrations of metallic copper dusts or fumes may cause nasal irritation and/or nausea, vomiting and stomach pain.

It is unlikely that the amount of particles that someone would be exposed to from firing would be sufficient to cause any of these effects.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Components	% By Weight	CAS Number	EINECS/ ELINCS #
Iron	0 – 97	7439-89-6	231-096-4
Copper	50 - 65	7440-50-8	231-159-6
Zinc	15 - 32	7440-66-6	231-175-3
Nitrocellulose	2 - 13	9004-70-0	Polymer
Nitroglycerin	0.5 - 2	55-63-0	200 – 240 -8
Lead styphnate	0.1 - 1	15245-44-0	239-290-0

4. FIRST AID MEASURES

Eye Contact: Immediately flush out fume or particles with large amounts of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. If eye irritation develops, call a physician at once.

Skin Contact: Wash skin with plenty of soap and water.

Inhalation: If symptoms of lung irritation occur (coughing, wheezing or breathing difficulty), remove from exposure area to fresh air immediately. If breathing has stopped, perform artificial respiration. Keep affected person warm and at rest. Get medical attention.

Ingestion: If ingested, immediately call a physician.

Medical Conditions Aggravated By Exposure:

There are no medical conditions known to be aggravated by exposure to this product in its solid form. Exposure to lead can aggravate anemia, cardiovascular and respiratory disease.

Recommendations To Physicians:

Remove from exposure, if possible, and treat symptoms

5. FIRE FIGHTING MEASURES

<i>PROPERTY</i>	<i>VALUE</i>	<i>PROPERTY</i>	<i>VALUE</i>
Explosive	Yes	Flammable	Not applicable
Combustible	Not applicable	Pyrophoric	No
Flash Point (°C):	Not applicable	Burning Rate of Material:	Not applicable
Lower Explosive Limit:	Not applicable	Autoignition Temp.:	No data
Upper Explosive Limit:	Not applicable	Flammability Classification: (defined by 29 CFR 1910.1200)	Explosive

Unusual Fire and Explosion Hazards:

Extinguishing Media:

Special Firefighting Procedures:

Possible projection hazard.

Flood area with water. If no water is available, carbon dioxide, dry chemical or earth may be used.


Do not fight fire when fire reaches cargo. Cargo may explode.

Firefighters must wear self-contained breathing apparatus (SCBA) and full protective equipment. Structural firefighters' protective clothing will only provide limited protection.


Isolate materials not yet involved in the fire. Move containers from fire area if possible; otherwise, cool with carefully applied water spray.

Prevent runoff water from entering storm drains, bodies of water, or other environmentally sensitive areas, if practical.

NFPA RATING SYSTEM



HMIS RATING SYSTEM

HEALTH HAZARD (BLUE)		0*	
FLAMMABILITY HAZARD (RED)		1	
PHYSICAL HAZARD (YELLOW)		2	
PROTECTIVE EQUIPMENT			
EYES	PPE CODE	RESPIRATORY	HEARING
	A	See Sect 8	See Sect 8

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe * = Chronic hazard

6. ACCIDENTAL RELEASE MEASURES

FOR ALL TRANSPORTATION ACCIDENTS, CALL CHEMTREC AT 800-424-9300.

Spill Response:

A spill of this material will normally not require emergency response team capabilities. If, however, a large spill occurs, call 1-888-289-1911 for technical assistance.

Accidental Release Procedures:

Spills of this material should be handled carefully. Do not subject materials to mechanical shock. Collect material and place in a designated, labeled waste container. See Section 13 for waste disposal.

7. HANDLING AND STORAGE

Precautions for Safe Handling:

Use appropriate personal protective equipment (see Section 8). Workers should wash hands thoroughly after handling. Eating, drinking and smoking should be prohibited in areas where this material is handled and stored.

Conditions for Safe Storage:

Store in accordance with local regulations. Store in original containers in a cool, dry location away from Acids, Class A & B explosives, strong oxidizers, and caustics. Avoid mechanical impact or shock and electrical discharge.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters:

CAS #	CHEMICAL NAME	ACGIH TLV	OSHA PEL	INTERNATIONAL OELS
7439-89-6	Iron	None established	None established	None established
7440-50-8	Copper	0.2 mg/m ³ (fume), 1 mg/m ³ (dusts and mists)	0.1 mg/m ³ (fume) 1 mg/m ³ (dusts and mists)	Austria, Belgium, Canada: 0.2 mg/m ³ (fumes), 1 mg/m ³ (dusts) Denmark: 1.0 mg/m ³ (dust and powder) Germany (MAK): 0.1 mg/m ³ (fume), 1 mg/m ³ (dusts and mists)
7440-66-6	Zinc	None established	None established	None established
9004-70-0	Nitrocellulose	None established	None established	None established

55-63-0	Nitroglycerin	0.05 ppm (0.46 mg/m ³) Skin	Ceiling – 0.2 ppm (2 mg/m ³) Skin	Denmark: 0.02 ppm (0.2 mg/m ³) Norway, Sweden: 0.03 ppm (0.3 mg/m ³) Austria, Belgium, Germany, The Netherlands, Poland, Switzerland: 0.05 ppm (0.47 mg/m ³), skin Finland, France: 0.1 ppm (0.9 mg/m ³), skin U.K.: 0.2 ppm (2 mg/m ³), skin
15245-44-0	Lead styphnate	None established	None established	None established

<u>Engineering Controls:</u>	Local exhaust ventilation is recommended if significant dusting occurs or fumes are generated. Otherwise, use general exhaust ventilation. Use explosion-proof ventilation.
<u>Respiratory Protection:</u>	Not normally needed. Maintain airborne contaminant concentrations below guidelines listed above. Use an appropriate approved air-purifying respirator equipped with HEPA cartridges/canisters where there is the potential for exceeding established occupational exposure limits.
<u>Eye/Face Protection:</u>	Use safety glasses.
<u>Hand Protection:</u>	Not normally needed
<u>Skin Protection:</u>	Not normally needed.
<u>Hearing Protection:</u>	Not normally needed. During firing use hearing protection.
<u>General Hygiene:</u>	Do not eat, drink, or smoke while using this product. Wash hands thoroughly after use.

9. PHYSICAL AND CHEMICAL PROPERTIES

PROPERTY	VALUE	PROPERTY	VALUE
<i>Appearance:</i>	Cylindrical brass cartridge	<i>Physical State:</i>	Solid
<i>Odor:</i>	None	<i>Odor Threshold:</i>	None
<i>Boiling Point (°F):</i>	Not applicable	<i>Melting point:</i>	Not applicable
<i>Vapor Pressure (mm Hg):</i>	Not applicable	<i>Freezing point:</i>	Not applicable
<i>Vapor Density (air = 1):</i>	Not applicable	<i>Bulk Density:</i>	Not applicable
<i>Specific gravity (g/cc):</i>	Not applicable	<i>Viscosity (cps):</i>	Not applicable
<i>pH:</i>	Not applicable	<i>Decomposition Temperature:</i>	Not applicable
<i>Solubility in Water (20 °C):</i>	Insoluble	<i>Evaporation Rate:</i>	Not applicable
<i>Volatiles, Percent by volume:</i>	Not applicable	<i>Octanol/water partition coefficient:</i>	Not applicable

10. STABILITY AND REACTIVITY

<u>Stability:</u>	Stable under normal temperatures and pressure.
<u>Possibility of Hazardous Reactions:</u>	Hazardous polymerization will not occur
<u>Incompatible Materials:</u>	Acids, Class A & B explosives, strong oxidizers, and caustics
<u>Hazardous Decomposition Products:</u>	Nitrogen oxides, carbon monoxide, lead oxides, carbon dioxide, lead dust/fume
<u>Conditions to Avoid:</u>	Contact with incompatible materials. Physical damage to containers; cartridges may detonate if case is punctured.

11. TOXICOLOGICAL INFORMATION

Potential Routes of Entry: Inhalation, Skin, and by Ingestion.

The physical nature of this product makes absorption from any route unlikely. A small amount of inhalable particles may be created when cartridge is fired.

Effects Of Acute Exposure:

PRODUCT		COMPONENTS					
		Lead styphnate	Nitroglycerin	Copper	Nitrocellulose	Iron	Zinc
Inhalation LC ₅₀	Particles generated from firing may be slightly toxic	No data	No data	No data	No data	No data	No data
Skin Contact LD ₅₀	Skin absorption unlikely	No data	> 280 mg/kg (rabbit)	375 mg/kg, sc (rabbit)	No data	No data	No data
Ingestion LD ₅₀	Ingestion unlikely	No data	105 mg/kg (rat)	3.5 mg/kg, ip (mouse)	> 5 g/kg (rat)	30 g/kg (rat)	No data

PRODUCT		COMPONENTS					
		Lead styphnate	Nitroglycerin	Copper	Nitrocellulose	Iron	Zinc
Irritation	Particles generated from firing may be slightly irritating to the eyes	No data	Mild eye and skin irritant	Respiratory irritant	No data	Eye irritant	Eye irritant
Sensitization	Sensitization to this Product has not been reported	No data	No data	No data	No data	No data	No data

Other Adverse Effects:Target Organ Toxicity:

No reported target organ toxicity from this product. Lead has caused nervous system, kidney and hematopoietic system damage in humans and laboratory animals.

Reproductive Toxicity:

This product is not known or reported to cause reproductive effects. Lead has been shown to reduce male reproductive function in humans and laboratory animals.

Teratogenicity (Birth Defects):

This product is not known or reported to cause developmental toxicity. Lead has been shown to affect fetal development including birth defects.

Mutagenicity:

This product is not known or reported to be mutagenic. Lead has been shown to be mutagenic in several *in vitro* assays.

Carcinogenicity:

IARC and US EPA list lead and lead compounds as probable human carcinogens (Group 2A) based on sufficient evidence from animal studies and limited evidence from human studies (epidemiology). NTP classifies lead and lead compounds as reasonably anticipated to be human carcinogens. Inorganic arsenic is causally associated with lung cancer via inhalation and skin cancer by ingestion. Arsenic is listed as a known human carcinogen by IARC (Group 1), OSHA, NTP and EPA

12. ECOLOGICAL INFORMATIONEnvironmental Effects:

PRODUCT: Product has not been tested for environmental properties.

COMPONENTS:

Copper:

Copper concentrations from 0.1 to 1.0 mg/l have been found to be not toxic for most fish. However, concentrations of 0.015 to 3.0 mg/l have been reported as toxic, particularly in soft water to many kinds of fish, crustacea, mollusks, insects, and plankton.

Lead:

LC 50 (48 hrs.) to bluegill is reported to be 2-5 mg/l. Lead is toxic to waterfowl.

Nitrocellulose:

LC₅₀ > 1000 mg/l to fish, invertebrates, and algae.

Nitroglycerin:

LC₅₀ = 1.228 mg/l to Bluegill, (96 hour, static)

Zinc:

The following concentrations of zinc have been reported as lethal to fish: 0.13 mg/l, for 12 – 24 hours to Rainbow trout fingerlings; 1.9 – 3.6 mg/l, 6 hr TLM (soft water, 30°C) to Bluegill Sunfish; 4 mg/l, 3 days (hard water) to Rainbow trout; 1 mg/l, 24 hours (soft water) to Sticklebacks.

The presence of copper appears to have a synergistic effect on the toxicity of zinc towards fish.

Environmental Fate:

MOBILITY:

Dissolved lead may migrate through soil.

PERSISTANCE/DEGRADABILITY:

Not biodegradable.

BIOACCUMULATION:

No data

13. DISPOSAL CONSIDERATIONS

Care must be taken to prevent environmental contamination from the use of this material. The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding the treatment, storage and disposal for hazardous and nonhazardous wastes.

14. TRANSPORT INFORMATION

Regulatory Information for US DOT, IATA, IMO, and ADR:

Proper Shipping Name	Cartridges for Tools, Blank	Cartridges, Power Device
Hazard Class Number and Description	Explosive 1.4S	Explosive 1.4S
UN Identification Number	UN0014	UN0323
Packing Group	PGII	PGII
DOT Label(s) Required	None	Explosive 1.4S

Marine Pollutant: None of the ingredients are classified by the DOT as a Marine Pollutant (as defined by 49 CFR 172.101, Appendix B)

Additional Information:

North American Emergency Response Guidebook Number (2004): 114

U.S. DEPARTMENT OF TRANSPORTATION SHIPPING REGULATIONS: This product is classified as dangerous goods under 49 CFR 172.101. Note: May be reclassified domestically as an ORM-D or Limited Quantity if packaged in accordance with 49 CFR 173.63.

TRANSPORT CANADA, TRANSPORTATION OF DANGEROUS GOODS REGULATIONS: This product is classified as Dangerous Goods.

INTERNATIONAL AIR TRANSPORT ASSOCIATION (IATA): This product is classified as Dangerous Goods.

INTERNATIONAL MARITIME ORGANIZATION (IMO) DESIGNATION: This product is classified as Dangerous Goods.

EUROPEAN AGREEMENT CONCERNING THE INTERNATIONAL CARRIAGE OF DANGEROUS GOODS BY ROAD (ADR): This product is classified by the United Nations Economic Commission for Europe to be dangerous goods.

15. REGULATORY INFORMATIONUS FEDERAL

TSCA	The components of this product are listed on the Toxic Substance Control Act inventory.				
CERCLA:	Copper, R.Q.* = 5000 lbs.; Zinc, R.Q. = 1000 lbs.; Nitroglycerin, R.Q. = 10 lbs; Lead, R.Q. = 10 lbs. (No reporting is required if diameter of the pieces of metal is equal to or exceeds 100 micrometers (0.004 inches).				
SARA 313:	Copper, Lead and Lead compounds, Nitroglycerin, Zinc (fume or dust)				
SARA 311/312:	<u>Health:</u>	Acute – No Chronic - No	<u>Fire:</u> No	<u>Reactivity:</u> Yes	<u>Release of Pressure:</u> No
SARA 302 EHS List:	None of the components of this product are listed.				

*RQ = Reportable Quantity

STATE RIGHT-TO-KNOW STATUS

Component	California	New Jersey	Pennsylvania	Massachusetts	Michigan
Iron	Not listed	Not listed	Not listed	Not listed	Not listed
Copper	Not listed	X	X	X	X
Zinc	Not listed	X	Not listed	X	X
Nitrocellulose	Not listed	X	X	X	Not listed
Nitroglycerin	Not listed	X	X	X	Not listed
Lead styphnate	X	Not listed	Not listed	X	Not listed

CALIFORNIA SAFE DRINKING WATER AND TOXIC ENFORCEMENT ACT (PROPOSITION 65)

Warning! This product contains detectable amounts of a chemical known to the State of California to cause cancer and/or birth defects or other reproductive harm.

GHS CLASSIFICATION

Carcinogenicity Category 1A
Reproductive Toxicity Category 1A
Explosive Division 1.4
STOT RE Category 1
Aquatic Environment, Chronic II

EUROPEAN REGULATIONS

Hazard Classification

Danger Symbols: E, T, N
Risk Phrases: R2, R48, R60, R63, R51/53
Safety Phrases: S2, S15, S20/21, S22, S39, S51, S61

German WGK Classification: Not known.

CANADIAN REGULATIONS

DSL/NDSL Inventory: The components of this product are on the DSL

IDL: Copper, Lead

CEPA PRIORITIES LIST: None

WHMIS: This product is not subject to WHMIS. It is regulated as a Class 6 Explosive in Canada.

JAPANESE REGULATIONS

Existing National Inventory of Chemical Substances (ENCS): The components of this product are listed

Japanese Priority Assessment Chemical Substances: None of the components of this product are listed

OTHER INTERNATIONAL CHEMICAL INVENTORIES

Swiss Giftliste List of Toxic Substances: All Components Listed
Australian Inventory (AICS): All Components Listed

16. OTHER INFORMATION

REVISIONS: 05
DATE: 02/28/2019
PREPARED BY: Olin Winchester, LLC
OTHER: Additional information available from: www.winchester.com

NOTICE: THE INFORMATION IN THIS SDS SHOULD BE PROVIDED TO ALL WHO WILL USE, HANDLE, STORE, TRANSPORT, OR OTHERWISE BE EXPOSED TO THIS PRODUCT. THIS INFORMATION HAS BEEN PREPARED FOR THE GUIDANCE OF PLANT ENGINEERING, OPERATIONS AND MANAGEMENT AND FOR PERSONS WORKING WITH OR HANDLING THIS PRODUCT. OLIN BELIEVES THIS INFORMATION TO BE RELIABLE AND CURRENT AS OF THE DATE OF PUBLICATION, BUT MAKES NO WARRANTY THAT IT IS.